

Product Specification Sheet



References

- 9100 Kit 1 Apt
- 9101 Kit 2 Apts
- 9102 Kit 4 Apts
- 9103 Kit 6 Apts
- 9104 Kit 8 Apts
- 9105 Kit 10 Apts
- 9106 Kit 12 Apts

Postmen box

- Ref 1050F Flush.
- Ref 1050S Surface.
- (H) 5" 1/8 x (L) 5" 1/8

Panels and backbox sizes

- KIT 1 & 2 APPTS.....Panels: (H) 5" 1/8 x (W) 5" 1/8
- KIT 1 & 2 APPTS.....Backbox: (H) 4" 1/2 x (W) 4" 9/16 x (D) 1" 5/8
- KIT 4 APPTS.....Panel: (H) 6" x (W) 5" 1/8
-Backbox: (H) 5" 1/2 x (W) 4" 9/16 x (D) 1" 5/8
- KIT 6 APPTS.....Panel: (H) 7" x (W) 5" 1/8
-Backbox: (H) 6" 3/8 x (W) 4" 9/16 x (D) 1" 5/8
- KIT 8 APPTS.....Panel: (H) 7" 15/16 x (W) 5" 1/8
-Backbox: (H) 7" 1/4 x (W) 4" 9/16 x (D) 1" 5/8
- KIT 10 APPTS.....Panels: (H) 9" 13/16 x (W) 5" 1/8
- KIT 12 APPTS.....Backbox: (H) 9"5/16 x (W) 4" 9/16 x (D) 1" 5/8

Surface box

- Ref 8951 Kits 1 & 2 appts.
- Ref 8952 Kits 3 & 4 appts.
- Ref 8953 Kit 6 appts.
- Ref 8954 Kit 8 appts.
- Ref 8955 Kits 10 & 12 appts



Citymax Kits

Installed in the accesses to the building, they enable communication with homes, door opening, guard unit call , etc.
CityLine is the "continuous profile" outdoor panel line for buildings. The PANELS are manufactured in anodized aluminium, highly resistant to rough weather and climate changes.

The panel design stands out for its curved-convex profile. A cellular rubber airtight seal included assures a perfect panel-to-wall fit to prevent water filtrations.

It is possible to combine two or more panels, as long as they are from the same series. For a perfect fit, a set of separators should be used for every two panels installed between their flush mounted boxes.

Colour aluminium

Call Pushbuttons: streamlined metallic shape in line with the panel's curved profile.

Pressing the call button is confirmed by an acoustic signal from the amplifier.

Equipped with special silver plated contacts that make them last longer. Pushbuttons include a card slot to insert a label with the home owner's name and door number. When the lighting key on the front of the amplifier is pressed, a soft light lets you see the card slots, even in total darkness.

Adjustable Amplifier, with two way volume control.

1- Lighting by leds.

2- Synthetised voice message

When the door is released, a message remind the visitor to close the door. This message can be expressed in different languages: **Spanish, English, French and German.**

3- Light sensor (lights goes on at night and off at day).

4- Output for magnetic lock.

Kits are available in gold color too.

Power 12 V.A.C or D.C

Each kit included:

Panel with amplifier, flush back box and # of handsets.

Transformer is included

Conventional System: uses wires common to the whole installation plus 1 call wire (or call return) per home..

Recommended in small to medium-sized buildings (up to 50 residents approx), with several accesses and central guard unit. For residential complexes with general entrance and interior blocks.

Wiring:

- Audio door entry system: 4 common wires + N (1 call wire per home).

- Video door entry system: 7 common wires + 1 video coaxial+N (1 call wire per home).

Maximum distance in the installation based on the cable section used (see technical manuals).

Rain Hood

- Ref 8400 Kits 1 & 2 appts.
- Ref 8401 Kits 3 & 4 appts.
- Ref 8402 Kit 6 appts.
- Ref 8403 Kit 8 appts.
- Ref 8404 Kits 10 & 12 appts

